



CORPORATE HEADQUARTERS

P.O. BOX 2069, BELLINGHAM, WA, U.S.A.

TELEPHONE: (360) 647-0801 • FAX: (360) 676-1075

## Introducing the Grizzly Model G0621X Vertical Wood/Metal Bandsaw



**Fully Balanced Cast-Iron  
Wheels**



**Blade Guides**

### **MACHINE HIGHLIGHTS (see *Machine Data Sheet for full specifications*)**

- 1¼ HP, 220V, 3-phase motor runs on single-phase, 220V power using frequency inverter.
- Variable frequency drive enables blade speed adjustments between 150 and 3000 FPM using control dial and digital readout.
- Cuts wood and metal stock up to 10" tall and 13½" left of blade using a 108" blade.
- Precision-ground cast iron table includes T-slots for miter gauge, and tilts from -5° to 45°.
- Rip fence includes right and left reading indicators, T-slots for quick change attachments, quick release, ball bearing slide, and rock-solid lock lever.
- Also features fully-balanced cast iron wheels with rubber tires, rack-and-pinion upper blade guide adjustment, quick release blade tension, and 2½" dust port.

The Model G0621X Vertical Wood/Metal Bandsaw is available for \$1,150.00. As with all Grizzly products, the Model G0621X is covered by a one-year warranty. For more information call 1-800-523-4777 or visit [www.grizzly.com](http://www.grizzly.com).



# MACHINE DATA SHEET

Customer Service #: (570) 546-9663 • To Order Call: (800) 523-4777 • Fax #: (800) 438-5901

## MODEL G0621X WOOD/METAL CUTTING BANDSAW

### Product Dimensions:

Weight ..... 261 lbs.  
 Length/Width/Height ..... 30" x 30" x 72½"  
 Footprint (Length/Width) ..... 27" x 15"

### Shipping Dimensions:

Type ..... Cardboard  
 Content ..... Machine  
 Weight ..... 271 lbs.  
 Length/Width/Height ..... 56" x 27" x 16"

### Electrical:

Required Power Source ..... 220V, Single-Phase  
 Switch ..... ON/OFF Push Button w/Large STOP Paddle  
 Cord Length ..... 6 ft.  
 Cord Gauge ..... 16 gauge  
 Recommended Circuit Size ..... 15 amp  
 Plug Included ..... No  
 Recommended Plug ..... 6-15

### Motor:

Horsepower ..... 1.25 HP  
 Voltage ..... 220V  
 Phase ..... 3-Phase  
 Cycle ..... 60 Hz  
 Type ..... Induction  
 Amps ..... 4.8  
 Speed ..... 1725 RPM  
 Bearings ..... Sealed and Lubricated  
 Power Transfer ..... Belt Drive

### Main Specifications:

Throat Capacity Left-of-Blade ..... 13½"  
 Maximum Resaw Height ..... 10"  
 Blade Speeds ..... Variable 150-3000 FPM  
 Blade Length ..... 108"  
 Blade Width Range ..... ½"-1"  
 Table Size (Length, Width, Thickness) ..... 16" x 20" x 1¾"  
 Table Tilt ..... -5° to 45°  
 Table Height from Floor ..... 38½"  
 Wheel Diameter ..... 14"  
 Number of Dust Ports ..... 1  
 Dust Port Size ..... 2.5"  
 Fence Locking Location ..... Front

**Construction Materials:**

Wheels ..... Cast Iron  
Wheel Covers ..... Steel  
Table ..... Precision Ground Cast Iron  
Fence ..... Aluminum  
Base ..... Steel  
Body ..... Steel  
Paint ..... Powder Coated

**Other Specifications:**

Compatible Shop Fox Mobile Base Available from Grizzly ..... G7315Z  
Country Of Origin ..... Taiwan  
Sound Rating ..... 74 dB  
Warranty ..... 1 Year  
Serial Number Location ..... ID Label on Center of Upper Wheel Cover  
Approximate Assembly & Setup Time ..... 1.5 Hours