



CORPORATE HEADQUARTERS

P.O. BOX 2069, BELLINGHAM, WA, U.S.A.

TELEPHONE: (360) 647-0801 • FAX: (360) 676-1075

Introducing the Grizzly Model G0656X 8" Jointer with Spiral Cutterhead



MACHINE HIGHLIGHTS (see Machine Data Sheet for full specifications)

- 3 HP, 220V, single-phase motor.
- Spiral cutterhead with indexable carbide inserts.
- Built-in mobile base.
- Easy-to-reach pedestal mounted switch with oversized OFF paddle.
- Precision handwheel-controlled beds and fence.

The Model G0656X is available for \$1,075.00 and is covered by a one-year warranty. For more information call 1-800-523-4777 or visit www.grizzly.com.



MACHINE DATA SHEET

Customer Service #: (570) 546-9663 • To Order Call: (800) 523-4777 • Fax #: (800) 438-5901

MODEL G0656X 8" JOINTER w/SPIRAL CUTTERHEAD & MOBILE BASE

Product Dimensions:

Weight 465 lbs.
Length/Width/Height 72½" x 26" x 47¼"
Foot Print (Length/Width)..... 26¾" x 16½"

Shipping Dimensions:

Box #1

Type..... Wood Crate
Content Machine
Weight 435 lbs.
Length/Width/Height 25" x 81" x 15"

Box #2

Type..... Cardboard
Content Stand
Weight 167 lbs.
Length/Width/Height 19" x 30" x 27"

Electrical:

Switch..... ON/OFF Push Button with Large OFF Paddle
Switch Voltage 220V
Cord Length 6 ft.
Cord Gauge 14 gauge
Minimum Circuit Size 20A
Included Plug No
Recommended Plug Type 6-20

Motors:

Main

Type..... TEFC Capacitor Start Induction
Horsepower 3 HP
Voltage 220V
Phase Single
Amps 15A
Speed 3450 RPM
Cycle..... 60 Hz
Number Of Speeds..... 1
Power Transfer V-Belt Drive
Bearings Shielded and Lubricated

Main Specifications:

Operation Information

Fence Length 34⅞"
Fence Width 1¼"
Fence Height 5"
Fence Stops 45, 90, and 135 deg.

Cutting Capacities

Bevel Jointing	Left & Right 45 deg.
Maximum Width of Cut	8"
Maximum Depth of Cut	1/8"
Maximum Rabbeting Depth	1/2"
Number of Cuts Per Minute	21,400

Cutterhead Information

Cutterhead Type	Spiral
Cutterhead Diameter	3"
Number of Cutter Spirals	4
Number of Indexable Cutters	40
Cutter Insert Type	Indexable Carbide
Cutter Insert Length	14mm
Cutter Insert Width	14mm
Cutter Insert Thickness2mm
Cutterhead Speed	5350 RPM

Table Information

Table Length	72 1/2"
Table Width	9"
Floor to Table Height	33 1/2"
Table Adjustment Type	Handwheels

Construction

Body Assembly Construction	Cast Iron
Stand Construction	One-Piece Steel Cabinet
Fence Assembly Construction	Cast Iron
Guard Construction	Die Cast Metal
Dovetailed Ways on Bed	Adjustable
Parallelogram	No

Other Information

Number of Dust Ports	1
Dust Port Size	4"
Mobile Base	Built-In

Other Specifications:

Country Of Origin	China
Warranty	1 Year
Serial Number Location	ID Label on Front of Stand
Assembly Time	1 Hour

Features:

- Built in Easy-to-Use Mobile Base
- Included Push Blocks
- Top Mount Switch Controls
- Super Long 72 1/2" Bed
- Handwheel Controlled Fence Adjustment
- Rabbeting Table