

Grizzly[®] Industrial

CORPORATE HEADQUARTERS

P.O. BOX 2069, BELLINGHAM, WA, U.S.A.

TELEPHONE: (360) 647-0801 • FAX: (360) 676-1075

Introducing the Grizzly Model G0699 12" Sliding Table Saw with Separate Scoring Motor



MACHINE HIGHLIGHTS (see Machine Data Sheet for full specifications)

- 7½ HP, 220V/440V, 3-phase main motor, and 1 HP, 220V/440V, 3-phase scoring motor.
- Handles workpieces up to 126" long x 126" wide.
- Cuts up to 3⁵/₁₆" deep at 90° and 2³/₈" deep at 45°.
- Features 4³/₄" scoring saw blade for tearout-free cuts.
- Sliding table travels on bearing guide system with hardened steel ways.
- Miter fence features two flip stops for repetitive cutting.
- Micro-adjustable aluminum rip fence can flip 90° for ripping thin laminates and veneers.
- Includes adjustable riving knife, and 5" main and 2½" blade guard dust hood.

The Model G0699 12" Sliding Table Saw is available for \$5,995.00. As with all Grizzly products, the Model G0699 is covered by a one-year warranty. For more information call 1-800-523-4777 or visit www.grizzly.com.



MACHINE DATA SHEET

Customer Service #: (570) 546-9663 · To Order Call: (800) 523-4777 · Fax #: (800) 438-5901

MODEL G0699 12" SLIDING TABLE SAW W/ SCORING

Product Dimensions:

Weight..... 1219 lbs.
 Length/Width/Height..... 139 x 133 x 45 in.
 Foot Print (Length/Width)..... 74-1/2 x 35-1/2 in.

Shipping Dimensions:

Carton #1

Type..... Wood
 Content..... Machine
 Weight..... 1236 lbs.
 Length/Width/Height..... 83 x 44. x 44 in.

Carton #2

Type..... Wood
 Content..... Sliding Table
 Weight..... 275 lbs.
 Length/Width/Height..... 132 x 20 x 18 in.

Electrical:

Power Requirement..... 220V/440V, 3-Phase, 60 Hz
 Minimum Circuit Size..... 30A @220, 15A @ 440V
 Switch..... Magnetic with Thermal Overload Protection
 Switch Voltage..... 220V
 Plug Included..... No
 Recommended Plug/Outlet Type..... L15-30 at 220V, Hardwire Disconnect Switch at 440V

Motors:

Scoring

Type..... TEFC Induction
 Horsepower..... 1 HP
 Voltage..... 220/440V
 Phase..... 3-Phase
 Amps..... 3A @220V, 1.5A @440
 Speed..... 3450
 Cycle..... 60 Hz
 Number Of Speeds..... 1
 Power Transfer Belt Drive
 Bearings..... Shielded and Permanently Sealed

Main

Type..... TEFC Induction
 Horsepower..... 7-1/2 HP
 Voltage..... 220/440V
 Prewired..... 220V
 Phase..... 3-Phase
 Amps..... 20A @220V, 10A @440V
 Speed..... 3450
 Cycle..... 60 Hz
 Number Of Speeds..... 1
 Power Transfer V-Belt
 Bearings..... Shielded and Permanently Sealed

Main Specifications:

Operation Information

Main Blade Size.....	12 in.
Main Arbor Size.....	1 in.
Scoring Blade Size.....	4-3/4 in. (120 mm)
Scoring Blade Arbor Size.....	20 mm
Main Blade Tilt.....	0-45 deg.
Main Blade Speed.....	4000 RPM
Scoring Blade Tilt.....	0-45 deg.
Scoring Blade Speed.....	8000 RPM

Cutting Capacities

Max Depth Of Cut At 90D.....	3-5/16 in.
Max Depth Of Cut At 45D.....	2-3/8 in.
Table With Rip Fence Max Cut Width.....	49-3/4 in.
Sliding Table With Cross Fence Max Cut Width.....	126 in.
Sliding Table With Cross Fence Max Cut Length.....	126 in.
Miter Fence Cut Width At 45D.....	126 in.

Table Information

Floor To Table Height.....	36 in.
Table Size Length.....	21-1/2 in.
Table Size Width.....	35-1/4 in.
Table Size Thickness.....	3 in.
Table Size With Ext Wings Length.....	59 in.
Table Size With Ext Wings Width.....	35-1/4 in.
Table Size With Ext Wings Thickness.....	3 in.
Sliding Table Length.....	126 in.
Sliding Table Width.....	14 in.

Fence Information

Fence Size Length.....	73 in.
Fence Size Width.....	2-3/8 in.

Construction Materials

Table Construction.....	Cast Iron
Sliding Table Construction.....	Aluminum
Base Construction.....	Cast Iron
Body Assembly Construction.....	Steel
Cabinet Construction.....	Steel
Trunnions Construction.....	Cast Iron
Rollers Construction.....	Steel
Fence Assembly Construction.....	Extruded Aluminum & Cast Iron
Rails Construction.....	Hardened Steel
Guard Construction.....	Plastic
Spindle Bearing Type.....	Lubricated & Permanently Sealed Ball Bearing
Paint.....	Powder Coated

Other Related Information

No Of Dust Ports.....	2
Dust Port Size.....	2-1/2, 5 in.

Other Specifications:

Country Of Origin	Taiwan
Warranty	1 Year
Serial Number Location	Machine ID Label on Side of Machine
Assembly Time	3 Hours
Sound Rating	82 dB

Features:

- Micro-adjustable rip fence
- Scoring blade for tear-out free cutting
- Sliding table on bearing guide system with hardened steel ways
- Aluminum alloy crosscut fence
- Miter fence with two swing stops for repetitive cutting
- Blade cover safety limit switch
- Adjustable riving knife

