

Grizzly[®] Industrial

CORPORATE HEADQUARTERS

P.O. BOX 2069, BELLINGHAM, WA U.S.A.

TELEPHONE: (360) 647-0801 • FAX: (360) 676-1075

Introducing the Grizzly Model G9968 7.5 HP Long Bed Shaper



MACHINE HIGHLIGHTS

- 7.5 HP, 220V/440V, 3-phase motor.
- Huge 99³/₄" x 33¹/₄" table with extension rail makes it easy to shape full-sized doors.
- 1¹/₄" Spindle with 5¹/₂" capacity under nut and 5" travel—accepts up to 11³/₄" diameter cutters.
- Precision-ground cast-iron micro-adjustable fence with adjustable steel guard.
- Spindle speeds of 5500, 7500, and 10,000 RPM.
- Emergency stop brake, spindle lock, and forward/reverse capabilities.
- Massive vibration-killing construction—weighs 1540 lbs!

The Model G9968 is available for \$4,695 and is covered by a one-year warranty. For more information call 1-800-523-4777 or visit www.grizzly.com.



MACHINE DATA SHEET

Customer Service #: (570) 546-9663 · To Order Call: (800) 523-4777 · Fax #: (800) 438-5901

MODEL G9968 7-1/2 HP SHAPER

Product Dimensions:

Weight..... 1540 lbs.
 Length/Width/Height..... 91-3/4 x 40 x 45 in.
 Foot Print (Length/Width)..... 35-5/8 x 29 in.

Shipping Dimensions:

Type..... Wood Crate
 Content..... Machine
 Weight..... 1832 lbs.
 Length/Width/Height..... 42 x 97 x 46 in.

Electrical:

Minimum Circuit Size..... 20 amp
 Switch..... Magnetic with Thermal Overload Protector
 Switch Voltage..... 220V
 Cord Length..... 4 ft.
 Cord Gauge..... 10 gauge
 Plug Included..... No
 Voltage Conversion Kit..... P9968700
 Phase Converter..... G7978

Motors:

Main

Type..... TEFC Induction
 Horsepower..... 7-1/2 HP
 Voltage..... 220/440V
 Prewired..... 220V
 Phase..... Three
 Amps..... 20/10A
 Speed..... 3450 RPM
 Cycle..... 60 Hz
 Number Of Speeds..... 1
 Power Transfer Belt Drive
 Bearings..... Shielded and Lubricated

Main Specifications:

Operation Info

Max. Cutter Height..... 5-1/2 in.
 Max. Cutter Dia..... 11-3/4 in.
 Spindle Sizes..... 1-1/4 in.
 Spindle Lengths..... 6 in.
 Exposed Spindle Length..... 6 in.
 Spindle Cap Under The Nut..... 5-1/2 in.
 Spindle Speeds..... 5500, 7500, 10000 RPM
 Spindle Travel..... 5 in.
 Spindle Openings..... 4-1/4, 8, 13 in.

Table Info

No. Of Table Inserts.....	2
Table Insert Sizes I.D.....	4, 8 in.
Table Insert Sizes O.D.....	8, 13 in.
Table Counterbore Diameter.....	13 in.
Table Size Length.....	99-3/4 in.
Table Size Width.....	33-1/4 in.
Table Size Thickness.....	4-1/2 in.
Floor To Table Height.....	33 in.
Table Fence Length.....	45-1/4 in.
Table Fence Width.....	23 mm
Table Fence Height.....	5-1/8 in.

Construction

Table Const.....	Ground Cast Iron
Base Const.....	Pre-Formed Steel
Body Assembly Const.....	Solid Steel
Cabinet Const.....	Pre-Formed Steel
Fence Const.....	Cast Iron with Wood
Miter Gauge Const.....	Cast Iron
Guard Const.....	Cast Iron
Spindle Bearings.....	Sealed and Lubricated
Paint.....	Powder Coated

Other

No. Of Dust Ports.....	1
Dust Port Size.....	5 in.

Other Specifications:

ISO Factory	ISO 9001
Country Of Origin	Taiwan
Warranty	1 Year
Serial Number Location	ID Label on Front of Cabinet
Assembly Time	20 minutes

Features:

- 4 Spring Hold-Down Assemblies
- Quick Release Levers and Knob Equipped Fence Adjustment
- 2 Table Inserts
- Spindles Include Spacer and Nuts
- Vertical Spindle Lock
- Spindle Brake
- Miter Gauge Included
- Includes Service Wrenches
- Three Spindle Speeds-5500, 7500, and 10,000 RPM
- Micro Adjusting Fence
- 6" Dust Port
- Front Table Pullout Extensions