



MACHINE DATA SHEET

Customer Service #: (570) 546-9663 · To Order Call: (800) 523-4777 · Fax #: (800) 438-5901

MODEL G0489 4 HP 220V 3-PHASE METALWORKING BELT SANDER

Product Dimensions:

Weight..... 188 lbs.
Width (side-to-side) x Depth (front-to-back) x Height..... 39 x 22-1/2 x 48 in.
Footprint (Length x Width)..... 20-3/4 x 13-3/4 in.

Shipping Dimensions:

Type..... Wood Crate
Content..... Machine
Weight..... 248 lbs.
Length x Width x Height..... 46 x 22 x 26 in

Electrical:

Minimum Circuit Size..... 15 amp
Switch..... Magnetic
Switch Voltage..... 220V
Cord Length..... 6 ft.
Cord Gauge..... 16 gauge
Plug Included..... No
Recommended Phase Converter..... G5843

Motors:

Main

Type..... TEFC
Horsepower..... 4 HP
Voltage..... 220V
Prewired..... 220V
Phase..... Three
Amps..... 11A
Speed..... 1725 RPM
Cycle..... 60 Hz
Number of Speeds..... 1
Power Transfer Direct Drive
Bearings..... Sealed, Permanently Lubricated

Main Specifications:

Belt Info

Sanding Belt Width..... 3 in.
 Sanding Belt Length..... 79 in.
 Sanding Belt Speed..... 3937 FPM
 Belt Arm Tilt..... 30 deg.
 Height Belt Arm Horizontal..... 40 in.
 Belt Release..... Quick Release
 Drive Roller Type..... Cast Aluminum
 Drive Roller Length..... 3 in.
 Drive Wheel Diameter..... 8 in.
 Idler Roller Type..... Rubber
 Idler Roller Length..... 3 in.
 Idler Roller Diameter..... 8 in.

Platen Info

Platen Type..... Graphite Coated
 Platen Length..... 20-1/2 in.
 Platen Width..... 3 in.

Construction

Base..... Formed Steel
 Stand..... Formed Steel
 Frame..... Formed Steel
 Paint..... Epoxy

Other

No. Of Dust Ports..... 1
 Dust Port Size..... 4 in.

Other Specifications:

Country Of Origin China
 Warranty 1 Year
 Serial Number Location ID Tag
 Assembly Time 30 minutes

Features:

- Single Knob Tracking Adjustment
- Spring Loaded Quick Release Belt
- Work Stop for Use With the Platen
- Work Rest for Use with the Contact Wheel