



MACHINE DATA SHEET

Customer Service #: (570) 546-9663 · To Order Call: (800) 523-4777 · Fax #: (800) 438-5901

MODEL G0547 4" X 36" BELT/6" DISC COMBO SANDER

Product Dimensions:

Weight..... 34 lbs.
Width (side-to-side) x Depth (front-to-back) x Height..... 17-1/2 x 14-3/8 x 23-3/4 in.
Footprint (Length x Width)..... 14-5/8 x 6-5/8 in.

Shipping Dimensions:

Type..... Cardboard Box
Content..... Machine
Weight..... 39 lbs.
Length x Width x Height..... 12 x 22 x 11 in.

Electrical:

Power Requirement..... 110V, Single-Phase, 60 Hz
Prewired Voltage..... 110V
Full-Load Current Rating..... 5A
Minimum Circuit Size..... 15A
Connection Type..... Cord & Plug
Power Cord Included..... Yes
Power Cord Length..... 4 ft.
Power Cord Gauge..... 18 AWG
Plug Included..... Yes
Included Plug Type..... 5-15
Switch Type..... Toggle Safety Switch w/Removable Key

Motors:

Main

Horsepower..... 1/3 HP
Phase..... Single-Phase
Amps..... 5A
Speed..... 3450 RPM
Type..... ODP Permanent-Split Capacitor
Power Transfer Belt Drive
Bearings..... Sealed & Permanently Lubricated
Centrifugal Switch/Contacts Type..... N/A

Main Specifications:

Belt Sander Info

Sanding Belt Width..... 4 in.
Sanding Belt Length..... 36 in.
Sanding Belt Speed..... 1970 FPM
Sanding Belt Tilt..... 90 deg.
Max Height of Belt in Vertical Position..... 23-3/4 in.
Belt Tension Release Type..... Quick Release
Platen Type..... Steel
Platen Length..... 12-1/4 in.
Platen Width..... 4-3/8 in.

Disc Sander Info

Disc Diameter..... 6 in.
Disc Speed..... 3450 RPM
Disc Sandpaper Backing Type..... PSA
Table Length..... 6-1/4 in.
Table Width..... 8-7/8 in.
Table Tilt..... Left 0, Right 45 deg.
Table-to-Floor Height..... 4-3/4 in.

Construction Materials

Base..... Cast Iron
Table..... Die-Cast Aluminum
Frame..... Cast Iron
Disc..... Aluminum
Miter Gauge..... Plastic/Steel Bar
Paint Type/Finish..... Powder Coated

Other Related Info

Miter Gauge Slot Width..... 5/8 in.
Miter Gauge Slot Height..... 1/4 in.
Number of Dust Ports..... 1
Dust Port Size..... 2-1/2 in.

Other Specifications:

Country of Origin China
Warranty 1 Year
Approximate Assembly & Setup Time 30 Minutes
Serial Number Location ID Label
ISO 9001 Factory No
Certified by a Nationally Recognized Testing Laboratory (NRTL) No

Features:

- Adjustable Miter Gauge
- Single Knob Tracking Adjustment
- Built In Dust Port
- Cast-Iron Construction