



MACHINE DATA SHEET

Customer Service #: (570) 546-9663 · To Order Call: (800) 523-4777 · Fax #: (800) 438-5901

MODEL G1014Z COMBINATION SANDER 6" X 48" BELT 9" DISC Z SERIES

Product Dimensions:

Weight..... 117 lbs.
Width (side-to-side) x Depth (front-to-back) x Height..... 30 x 24 x 56 in.
Footprint (Length x Width)..... 23 x 19 in.

Shipping Dimensions:

Type..... Cardboard
Content..... Machine
Weight..... 122 lbs.
Length x Width x Height..... 29 x 19 x 15 in.

Electrical:

Minimum Circuit Size..... 20 amp
Switch..... Safety Key Type
Switch Voltage..... 110V
Cord Length..... 6 ft.
Cord Gauge..... 16 gauge
Plug Included..... Yes

Motors:

Main

Type..... TEFC Capacitor Start Induction
Horsepower..... 3/4 HP
Voltage..... 110/220V
Prewired..... 110V
Phase..... Single
Amps..... 12/6A
Speed..... 3450 RPM
Cycle..... 60 Hz
Number of Speeds..... 1
Power Transfer Belt Drive
Bearings..... Sealed and Permanently Lubricated

Main Specifications:

Table Info

Table Tilt..... 0 - 45 deg.
Floor To Table Height..... 35 in.
Miter Gauge Slot Width..... 3/4 in.
Miter Gauge Slot Height..... 13/32 in.
Disc Table Length..... 12-1/4 in.
Disc Table Width..... 6 in.
Disc Table Thickness..... 1 in.

Belt Info

| | |
|---------------------------------|---------------|
| Sanding Belt Width..... | 6 in. |
| Sanding Belt Length..... | 48 in. |
| Sanding Belt Speed..... | 2300 FPM |
| Belt Arm Tilt..... | 0 - 90 deg. |
| Height Belt Arm Horizontal..... | 40 in. |
| Height Belt Arm Vertical..... | 56 in. |
| Belt Release..... | Quick Release |
| Drive Roller Type..... | Aluminum |
| Drive Roller Length..... | 6 in. |
| Drive Wheel Diameter..... | 3-1/2 in. |
| Idler Roller Type..... | Aluminum |
| Idler Roller Length..... | 6 in. |
| Idler Roller Diameter..... | 3-1/2 in. |

Spindle Info

| | |
|-------------------------|------------|
| Arbor Size..... | 5/8 in. |
| Total Arbor Length..... | 11-1/2 in. |

Disc Info

| | |
|----------------------------|----------|
| Sanding Disc Diameter..... | 9 in. |
| Sanding Disc Speed..... | 3450 RPM |

Platen Info

| | |
|--------------------|-----------------|
| Platen Type..... | Graphite Coated |
| Platen Length..... | 17 in. |
| Platen Width..... | 6-1/4 in. |

Construction

| | |
|------------------|--------------------------------|
| Base..... | Cast Iron |
| Stand..... | Preformed Steel |
| Table..... | Cast Iron |
| Frame..... | Cast Iron |
| Disc..... | Cast Iron |
| Miter Gauge..... | Die Cast Aluminum/Aluminum Bar |
| Paint..... | Epoxy |

Other

| | |
|------------------------|--------------|
| No. Of Dust Ports..... | 2 |
| Dust Port Size..... | 2, 2-1/2 in. |
| Mobile Base..... | G7314Z |

Other Specifications:

| | |
|------------------------------|---|
| Country Of Origin | Taiwan |
| Warranty | 1 Year |
| Serial Number Location | ID Label on Front of Stand, Above Grizzly Nameplate |
| Awards | Wood Magazine Best Value 1998 |
| Assembly Time | 1-1/2 hours |

Features:

- 2" Dust Port for Belt and 2-1/2" Dust Port for Disc
- Quick Belt Release
- Work Table Mounts for Use on Disc or Belt
- Single Knob Tracking
- Cast Iron Table
- Graphite Coated Platen
- Sturdy Steel Stand