



MACHINE DATA SHEET

Customer Service #: (570) 546-9663 · To Order Call: (800) 523-4777 · Fax #: (800) 438-5901

MODEL G7297 12" DISC SANDER

Product Dimensions:

Weight..... 66 lbs.
Width (side-to-side) x Depth (front-to-back) x Height..... 18 x 17-3/8 x 14-1/2 in.
Footprint (Length x Width)..... 13 x 10 in.

Shipping Dimensions:

Type..... Cardboard Box
Content..... Machine
Weight..... 67 lbs.
Length x Width x Height..... 18 x 20 x 17 in.

Electrical:

Power Requirement..... 110V, Single-Phase, 60 Hz
Prewired Voltage..... 110V
Full-Load Current Rating..... 10A
Minimum Circuit Size..... 15A
Connection Type..... Cord & Plug
Power Cord Included..... Yes
Power Cord Length..... 5 ft.
Power Cord Gauge..... 16 AWG
Plug Included..... Yes
Included Plug Type..... 5-15
Switch Type..... Toggle Safety Switch w/Removable Key

Motors:

Main

Horsepower..... 1 HP
Phase..... Single-Phase
Amps..... 10A
Speed..... 1725 RPM
Type..... TEFC Capacitor-Start Induction
Power Transfer..... Direct Drive
Bearings..... Sealed & Permanently Lubricated

Main Specifications:

Disc Sander Info

Disc Diameter..... 12 in.
Disc Speed..... 1750 RPM
Disc Sandpaper Backing Type..... PSA
Table Length..... 17-1/4 in.
Table Width..... 8-1/4 in.
Table Thickness..... 1 in.
Table Tilt..... Left 0, Right 45 deg.
Table-to-Floor Height..... 6-3/4 in.

Construction Materials

Base..... Cast Iron
Table..... Aluminum
Frame..... Steel
Disc..... Aluminum
Miter Gauge..... Plastic/Aluminum Bar
Paint Type/Finish..... Epoxy

Other Related Info

Miter Gauge Slot Width..... 10 mm
Miter Gauge Slot Height..... 18 mm
Number of Dust Ports..... 1
Dust Port Size..... 2 in.

Other Specifications:

Country of Origin China
Warranty 1 Year
Approximate Assembly & Setup Time 15 Minutes
ISO 9001 Factory No
Certified by a Nationally Recognized Testing Laboratory (NRTL) No

Features:

- Locking Miter Bar
- Built-In Dust Port
- Non-Slip Rubber Feet
- Compact and Completely Portable