



MACHINE DATA SHEET

Customer Service #: (570) 546-9663 · To Order Call: (800) 523-4777 · Fax #: (800) 438-5901

MODEL G9933 THREE SPINDLE SHAPER

Product Dimensions:

Weight..... 1185 lbs.
Width (side-to-side) x Depth (front-to-back) x Height..... 45-1/2 x 52-1/8 x 45 in.
Footprint (Length x Width)..... 37-1/4 x 34-1/4 in.

Shipping Dimensions:

Type..... Wood Crate
Content..... Machine
Weight..... 1260 lbs.
Length x Width x Height..... 50 x 54 x 43 in.

Electrical:

Minimum Circuit Size..... 30 amp
Switch..... Magnetic with Thermal Overload Protector
Switch Voltage..... 220V
Plug Included..... No

Motors:

Main

Type..... TEFC Capacitor Start Induction
Horsepower..... 3 HP
Voltage..... 220V
Prewired..... 220V
Phase..... Single
Amps..... 18A
Speed..... 3450 RPM
Cycle..... 60 Hz
Number of Speeds..... 1
Power Transfer Belt Drive
Bearings..... Shielded and Lubricated

Main Specifications:

Operation Info

Max. Cutter Height..... 4-9/16 in.
Max. Cutter Dia..... 6 in.
Spindle Sizes..... 1-1/4 in.
Spindle Lengths..... 5-7/8 in.
Exposed Spindle Length..... 4 in.
Spindle Cap Under The Nut..... 4-1/2 in.
Spindle Speeds..... 7000, 10000 RPM
Spindle Travel..... 4 in.
Spindle Openings..... 3-1/4, 6-1/4, 8-1/4 in.

Table Info

No. of Table Inserts.....	2
Table Insert Sizes I.D.....	3-1/8, 6-1/4 in.
Table Insert Sizes O.D.....	7-1/4, 9-3/16 in.
Table Counterbore Diameter.....	8-1/4 in.
Table Counterbore Depth.....	3/8 in.
Table Size Length.....	28-1/4 in.
Table Size Width.....	21-3/4 in.
Table Size Thickness.....	3-1/16 in.
Floor To Table Height.....	35 in.
Table Fence Length.....	27-1/8 in.
Table Fence Width.....	13/16 in.
Table Fence Height.....	3-7/8 in.

Miter Gauge Info

Miter Angle.....	90 - 30 deg.
Miter Gauge Slot Type.....	T-Slot
Miter Gauge Slot Width.....	3/4 in.
Miter Gauge Slot Height.....	7/8 in.

Construction

Table.....	Ground Cast Iron
Base.....	Pre-Formed Steel
Body Assembly.....	Cast Iron
Cabinet.....	Pre-Formed Steel
Fence.....	Cast Iron with Wood
Miter Gauge.....	Cast Iron
Guard.....	Cast Iron
Spindle Bearings.....	Sealed and Lubricated
Paint.....	Epoxy

Other

No. of Dust Ports.....	1
Dust Port Size.....	4 in.

Other Specifications:

Country Of Origin	Taiwan
Warranty	1 Year
Serial Number Location	ID Label on Front of Cabinet
Assembly Time	60 minutes

Features:

- 3 Separate Motors
- 3 Micro Adjustable Fences
- 3 Magnetic Reversing Switches
- Spindles Include Spacer and Nuts
- Vertical Spindle Lock
- Spindle Turning Lock
- Heavy Duty Miter Gauge Included
- Includes Service Wrenches and Tool Box
- Router Bit Spindle Available as an Option
- 3/4" and 1/2" Spindles Available as an Option
- Three 4" Dust Ports
- Two Spindle Speeds-7,000 & 10,000 RPM